

System	HFMP (Monopod) + TH-X H (Head) + TH-X Bowl clamp + HFMP Carrying case		
Payload	4 kg / 9 lb (*1)	TH-X H	
Weight	2.7kg / 5.9 lb	Tilt-Pan angle	Tilt: +90° / -80° , Pan: 360°
Height	① H: 1895 mm W: 380 mm (※Reference)	Counterbalance	FIX
	② H: 875 mm W: 380 mm (")	Drag mode	FIX
	③ L: 870 mm (")	Temperature range	-20°C to +60°C / -4°F to +140°F
Folded length	L: 622 mm (Shortest length for carrying)	Head base	Ball ø65 mm / Flat base with 3/8" female thread
	Camera plate (Sliding range)	Sliding plate (*2) ±30 mm / ±1.2"	HFMP
Plate attachment (Screw sliding range)	1/4-20UNC screw with video pin	Tilt-Pan angle	Tilt: ±20° (When unlocked), Pan: 360°
	68 mm / 2.7"	Pipe diameters	Upper:ø34 mm / middle:ø29.5 mm / Lower:ø25 mm
Monopod camera screw	3/8-16UNC	Section	2 STAGE
Pan handle	Unique pan handle (Non-telescopic)	Monopod fixation	Fixing flip lock levers
		Pipe materials	Aluminum

Remarks

(*1) The monopod's maximum payload does not guarantee a monopod's free-stand position.

(*2) Available for Manfrotto and Sachtler video heads. ※ Not available for all models of Manfrotto and Sachtler.

Do not use the monopod without the free-stand base, this may cause damage to product.

■ Exterior Dimensions (mm)

■ HFMP (Shortest length for carrying)

■ TH-X H

